# Author Index


| | | |
|---|---|---|
| Abd Alla, G. H. | Exhaust emissions from an indirect injection dual-fuel engine | 333–340 |
| Abdel-Halim, N. A. | Performance of multicone synchronizers for manual transmissions | 56–65 |
| Abd Rabbo, M. F. | Exhaust emissions from an indirect injection dual-fuel engine | 333–340 |
| Abul Masrur, M. | Rotational sensorless scalar control of three-phase induction motors and its application to automotive electric power assist steering | 33–34 |
| Aoki, T. | Comparison of the Q3 and Hybrid III 3-year-old dummy head and neck response during side air bag loading | 675–684 |
| Arumugham, S. | Fabrication and characterization of polyurethane-coated fabrics for collapsible diesel tanks | 487–491 |
| Ashcroft, S. J. | Ignition source characteristics for natural-gas-burning vehicle engines | 171–180 |
| Ashcroft, S. J. | A comparison of the relative effects of fuel composition and ignition energy on the early stages of combustion in a natural gas spark ignition engine using simulation | 383–393 |
| Atkinson, C. M. | Neural network modelling of the emissions and performance of a heavy-duty diesel engine | 111–126 |
| Austin, L. | A review of current sensor technologies and applications within automotive and traffic control systems | 589–614 |
| Austin, L. | Recent advances in antilock braking systems and traction control systems | 625–638 |
| Badr, O. A. | Exhaust emissions from an indirect injection dual-fuel engine | 333–340 |
| Bae, C. | Flow characteristics of misfired gas in the exhaust manifold of a spark ignition engine | 373–381 |
| Bae, C. S. | Importance of inter-ring crevice volume as a source of unburned hydrocarbon emissions—numerical considerations | 395–403 |
| Bae, C. S. | Speciated hydrocarbon emissions from a gas-fuelled spark-ignition engine with various operating parameters | 795–808 |
| Bakhshan, Y. | The $k$–$\varepsilon$ turbulence modelling of heat transfer and combustion processes in a Texaco controlled combustion stratified charge engine | 149–158 |
| Ball, R. J. | Fuzzy modelling approach to the prediction of journey parameters for hybrid electric vehicle control | 875–885 |
| Barnard, R. H. | Theoretical and experimental investigation of the aerodynamic drag due to automotive cooling systems | 919–927 |
| Barton, D. C. | Performance of multicone synchronizers for manual transmissions | 55–65 |
| Barton, D. C. | The frontal impact response of a spaceframe chassis sportscar | 865–873 |
| Bartz, W. J. | Gear oil influences on efficiency of gear and fuel economy of cars | 189–196 |
| Belmont, M. R. | Ignition source characteristics for natural-gas-burning vehicle engines | 171–180 |
| Belmont, M. R. | A comparison of the relative effects of fuel composition and ignition energy on the early stages of combustion in a natural gas spark ignition engine using simulation | 383–393 |
| Ben-Ari, J. | Vibration monitoring as a predictive maintenance tool for reciprocating engines | 895–903 |
| Bergman, F. | The effect of reduced contact area on the occurrence of disc brake squeals for an automotive brake pad | 561–568 |
| Bilal, I. M. | Fabrication and characterization of polyurethane-coated fabrics for collapsible diesel tanks | 487–491 |
| Boatto, P. | Internal combustion engine waste heat potential for an automotive absorption system of air conditioning. Part 1: tests on the exhaust system of a spark-ignition engine | 979–982 |
| Boatto, P. | Internal combustion engine waste heat potential for an automotive absorption system of air conditioning. Part 2: the automotive absorption system | 983–990 |
| Boccaletti, G. | Internal combustion engine waste heat potential for an automotive absorption system of air conditioning. Part 1: tests on the exhaust system of a spark-ignition engine | 979–982 |
| Boccaletti, G. | Internal combustion engine waste heat potential for an automotive absorption system of air conditioning. Part 2: the automotive absorption system | 983–990 |
| Böcking, J. | Differential evolution based identification of automotive hydraulic engine mount model parameters | 249–264 |
| Borrmeister, J. | Thermodynamics and charge exchange of the new BMW six-cylinder engine | 935–947 |
| Botsaris, P. N. | Ambient temperature influence on catalytic outlet–inlet temperature difference | 95–100 |
| Buckberry, C. H. | A study of brake disc modal behaviour during squeal generation using high-speed electronic speckle pattern interferometry and near-field sound pressure measurements | 285–296 |
| Cebon, D. | Theoretical investigation into the use of controllable suspensions to minimize road damage | 13–31 |
| Cerri, G. | Internal combustion engine waste heat potential for an automotive absorption system of air conditioning. Part 1: tests on the exhaust system of a spark-ignition engine | 979–982 |


© IMechE 2000

| | | |
|---|---|---|
| Cerri, G. | Internal combustion engine waste heat potential for an automotive absorption system of air conditioning. Part 2: the automotive absorption system | 983–990 |
| Chan, S. H. | Heat transfer and chemical kinetics in the exhaust system of a cold-start engine fitted with a three-way catalytic converter | 765–777 |
| Chan, T. L. | Multidimensional numerical simulation of heat radiation in direct injection diesel engines | 453–466 |
| Chao, H.-C. | Fuzzy logic controller for a vehicle active suspension system | 1–12 |
| Chen, S. | Multidimensional numerical simulation of heat radiation in direct injection diesel engines | 453–466 |
| Cheng, Z. | Limiting performance of seat belt systems for the prevention of thoracic injuries | 127–139 |
| Chirwa, E. C. | Airbag head restraint system | 229–241 |
| Chirwa, E. C. | Fuzzy ignition timing control for a spark ignition engine | 297–306 |
| Cho, H. | Measurements of cycle resolved air–fuel ratio near the spark plug in a spark ignition engine | 421–434 |
| Cho, H. | Prediction of the air–fuel ratio in transient conditions using a model of liquid fuel behaviour in the intake port of a spark-ignition engine | 731–740 |
| Choi, S. | Flow characteristics of misfired gas in the exhaust manifold of a spark ignition engine | 373–381 |
| Choi, S. M. | Importance of inter-ring crevice volume as a source of unburned hydrocarbon emissions—numerical considerations | 395–403 |
| Chow, A. | Modelling the monolithic exhaust converter/fuel reformer reactor—a zonal approach | 905–917 |
| Chung, Y. | Flow characteristics of misfired gas in the exhaust manifold of a spark ignition engine | 373–381 |
| Clark, N. N. | Neural network modelling of the emissions and performance of a heavy-duty diesel engine | 111–126 |
| Cole, D. J. | Theoretical investigation into the use of controllable suspensions to minimize road damage | 13–31 |
| Combes, E. | Simulation and assessment of power control strategies for a parallel hybrid car | 705–717 |
| Cordes, J. | Fluid–structure interaction in crash simulation | 669–673 |
| Cornish, R. | A novel approach to optimizing and stabilizing interior noise quality in vehicles | 685–692 |
| Crandall, J. R. | Simulation and assessment of power control strategies for a parallel hybrid car | 705–717 |
| Crandall, J. R. | Comparison of the Q3 and Hybrid III 3-year-old dummy head and neck response during side air bag loading | 675–684 |
| Crane, R. I. | Light-duty diesel exhaust after-treatment by a multicyclone particulate separator with an oxidation catalyst | 741–749 |
| Crolla, D. A. | Performance of multicone synchronizers for manual transmissions | 55–65 |
| Crolla, D. A. | A study of a Kalman filter active vehicle suspension system using correlation of front and rear wheel road inputs | 493–502 |
| Deacon, M. | The development of a sub-3 litre/100 km passenger car | 827–837 |
| deBotton, G. | Vibration monitoring as a predictive maintenance tool for reciprocating engines | 895–903 |
| Decker, F. | Fluid–structure interaction in crash simulation | 669–673 |
| Delhom, M. | Simulation and assessment of power control strategies for a parallel hybrid car | 705–717 |
| Delprat, S. | Simulation and assessment of power control strategies for a parallel hybrid car | 705–717 |
| de Pennington, A. | The frontal impact response of a spaceframe chassis sportscar | 665–873 |
| Dominy, R. G. | The influence of slipstreaming on sports prototype race car performance | 887–894 |
| Dukkipati, R. V. | Analysis of driveline loads in an automotive powertrain with multiple Cardan joints | 509–522 |
| Duma, S. M. | Comparison of the Q3 and Hybrid III 3-year-old dummy head and neck response during side air bag loading | 675–684 |
| Dziama, A. | Performance of an hydraulically restricted differential of a spur gear type | 67–73 |
| Edwards, C. | A study of brake disc modal behaviour during squeal generation using high-speed electronic speckle pattern interferometry and near-field sound pressure measurements | 285–296 |
| Eriksson, M. | The effect of reduced contact area on the occurrence of disc brake squeals for an automotive brake pad | 561–568 |
| Fawcett, J. N. | A method of measuring the dynamic loads in high-speed timing chains | 217–226 |
| Fraser, G. | A study of exhaust noise in a motor vehicle using statistical energy analysis | 75–83 |
| Frihi, D. | Comparison of the dynamic behaviour of the two misaligned crankshaft bearings | 991–997 |
| Fujiwara, Y. | Evaluating waste vegetable oils as a diesel fuel | 141–148 |
| Giacomin, J. | Differential evolution based identification of automotive hydraulic engine mount model parameters | 249–264 |
| Gimenez, F. | Evaluation of exhaust gas recirculation as a technique for reducing diesel engine $NO_x$ emissions | 85–93 |
| Glennie, D. | A method of measuring the dynamic loads in high-speed timing chains | 217–226 |
| Goel, V. K. | Rolling dynamic stiffness and damping characteristics of small-sized pneumatic tyres | 243–248 |
| Golenko, A. | Performance of an hydraulically restricted differential of a spur gear type | 67–73 |
| Guerra, T. M. | Simulation and assessment of power control strategies for a parallel hybrid car | 705–717 |
| Hale, J. M. | A method of measuring the dynamic loads in high-speed timing chains | 217–226 |
| Hampo, R. J. | Rotational sensorless scalar control of three-phase induction motors and its application to automotive electric power assist steering | 33–44 |
| Hanzevack, E. | Neural network modelling of the emissions and performance of a heavy-duty diesel engine | 111–126 |



© IMechE 2000

| | | |
|---|---|---|
| Hao, S. H. | Influence of performance characteristic of a gaseous fuel supply system on hydrocarbon emissions of a dual-fuel engine | 973–977 |
| Harouadi, F. | Comparison of the dynamic behaviour of the two misaligned crankshaft bearings | 991–997 |
| Heidrich, M. | Differential evolution based identification of automotive hydraulic engine mount model parameters | 249–264 |
| Henson, J. C. | Full-cycle firing simulation of a pent-roof spark-ignition engine with visualization of the flow structure, flame propagation and radiative heat flux | 957–971 |
| Hernandez, J. J. | Evaluation of exhaust gas recirculation as a technique for reducing diesel engine $NO_x$ emissions | 85–93 |
| Hoang, D. L. | Heat transfer and chemical kinetics in the exhaust system of a cold-start engine fitted with a three-way catalytic converter | 765–777 |
| Holmes, K. | Fuzzy ignition timing control for a spark ignition engine | 297–306 |
| Hong, J. | Handling and driving characteristics for six-wheeled vehicles | 159–170 |
| Horrocks, R. W. | The development of a sub-3 litre/100 km passenger car | 827–837 |
| Hsu, C.-H. | Epicyclic gear trains for automotive automatic transmissions | 523–532 |
| Hsu, J.-J. | Epicyclic gear trains for automotive automatic transmissions | 523–532 |
| Hu, J. | In-cylinder studies of the effects of $CO_2$ in exhaust gas recirculation on diesel combustion and emissions | 405–419 |
| Huang, S.-J. | Fuzzy logic controller for a vehicle active suspension system | 1–12 |
| Huang, Z. | Combustion characteristics and hydrocarbon emissions of a spark ignition engine fuelled with gasoline–oxygenate blends | 341–346 |
| Huang, Z. H. | Study on the performance and emissions of a compression ignition engine fuelled with dimethyl ether | 101–106 |
| Huang, Z. H. | Investigation on emission characteristics of a compression ignition engine with oxygenated fuels and exhaust gas recirculation | 503–508 |
| Huh, K. | Handling and driving characteristics for six-wheeled vehicles | 159–170 |
| Huh, K. Y. | Numerical simulation of intake and compression flow in a four-valve pent-roof spark ignition engine and validation with LDV data | 361–372 |
| Huh, K. Y. | Experimental study on the combustion characteristics of emulsified diesel in a rapid compression and expansion machine | 579–586 |
| Hwang, S.-H. | Prediction of the air–fuel ratio in transient conditions using a model of liquid fuel behaviour in the intake port of a spark-ignition engine | 731–740 |
| Jacobson, S. | The effect of reduced contact area on the occurrence of disc brake squeals for an automotive brake pad | 561–568 |
| Jang, W.-J. | Development of a general-purpose program based on the concept of subsystem assembly for the analysis of dynamic characteristics of a power transmission system | 545–560 |
| Jeon, S. Y. | Low-temperature drive characteristics of automotive power window systems | 843–849 |
| Jiang, D. | Combustion characteristics and hydrocarbon emissions of a spark ignition engine fuelled with gasoline–oxygenate blends | 341–346 |
| Jiang, D. M. | Study on the performance and emissions of a compression ignition engine fuelled with dimethyl ether | 101–106 |
| Jiang, D. M. | Investigation on emission characteristics of a compression ignition engine with oxygenated fuels and exhaust gas recirculation | 503–508 |
| Jo, H.-S. | Development of a general-purpose program based on the concept of subsystem assembly for the analysis of dynamic characteristics of a power transmission system | 545–560 |
| Jones, R. P. | Fuzzy modelling approach to the prediction of journey parameters for hybrid electric vehicle control | 875–885 |
| Jones, T. B. | Automotive box section design under torsion. Part 1: finite element modelling strategy | 347–359 |
| Jones, T. B. | Automotive box section design under torsion. Part 2: behaviour and implications on weight reduction | 473–485 |
| Kang, K. Y. | Numerical simulation of intake and compression flow in a four-valve pent-roof spark ignition engine and validation with LDV data | 361–372 |
| Kim, C. | Reduced-order modelling and parameter estimation for a quarter-car suspension system | 851–864 |
| Kim, C. G. | Importance of inter-ring crevice volume as a source of unburned hydrocarbon emissions—numerical considerations | 395–403 |
| Kim, C. U. | Speciated hydrocarbon emissions from a gas-fuelled spark-ignition engine with various operating parameters | 795–808 |
| Kim, E. S. | Prediction of knock onset and the autoignition site in spark-ignition engines | 751–763 |
| Kim, H. | Flow characteristics of misfired gas in the exhaust manifold of a spark ignition engine | 373–381 |
| Kim, J. | Handling and driving characteristics for six-wheeled vehicles | 159–170 |
| Kim, J.-H. | Elastic foundation effects on the dynamic response of engine mount systems | 45–53 |
| Kim, K. H. | Low-temperature drive characteristics of automotive power window systems | 843–849 |
| Kim, W. T. | Numerical simulation of intake and compression flow in a four-valve pent-roof spark ignition engine and validation with LDV data | 361–372 |
| Kitching, K. J. | Theoretical investigation into the use of controllable suspensions to minimize road damage | 13–31 |


© IMechE 2000

| | | |
|---|---|---|
| Krishna, M. V. S. M. | Performance evaluation of non-edible vegetable oils as substitute fuels in low heat rejection diesel engines | 181–187 |
| Krishna, V. | Analysis of driveline loads in an automotive powertrain with multiple Cardan joints | 509–522 |
| Kyprianou, A. | Differential evolution based identification of automotive hydraulic engine mount model parameters | 249–264 |
| Ladommatos, N. | The effect of aromatic hydrocarbons and oxygenates on diesel engine emissions | 307–332 |
| Ladommatos, N. | In-cylinder studies of the effects of $CO_2$ in exhaust gas recirculation on diesel combustion and emissions | 405–419 |
| Ladommatos, N. | Effects of fuels with a low aromatic content on diesel engine exhaust emissions | 779–794 |
| Lahmar, M. | Comparison of the dynamic behaviour of the two misaligned crankshaft bearings | 991–997 |
| Landsborough, K. L. | Stochastic prediction of cycle-by-cycle cylinder pressure fluctuations in a spark ignition engine | 435–451 |
| Lansdown, T. C. | Driver visual allocation and the introduction of intelligent transport systems | 645–652 |
| Lapuerta, M. | Evaluation of exhaust gas recirculation as a technique for reducing diesel engine $NO_x$ emissions | 85–93 |
| Latchford, J. | Airbag head restraint system | 229–241 |
| Leduc, B. | Idle regulation strategies using stepper motor idle valves: observation on engine simulator | 569–578 |
| Lee, J. | Measurements of cycle resolved air–fuel ratio near the spark plug in a spark ignition engine | 421–434 |
| Lee, J.-H. | Prediction of the air–fuel ratio in transient conditions using a model of liquid fuel behaviour in the intake port of a spark-ignition engine | 731–740 |
| Lee, J.-M. | Elastic foundation effects on the dynamic response of engine mount systems | 45–53 |
| Lee, J.-M. | Development of a general-purpose program based on the concept of subsystem assembly for the analysis of dynamic characteristics of a power transmission system | 545–560 |
| Lee, J. W. | Numerical simulation of intake and compression flow in a four-valve pent-roof spark ignition engine and validation with LDV data | 361–372 |
| Lee, K. | Measurements of cycle resolved air–fuel ratio near the spark plug in a spark ignition engine | 421–434 |
| Lee, M. M. K. | Automotive box section design under torsion. Part 1: finite element modelling strategy | 347–359 |
| Lee, M. M. K. | Automotive box section design under torsion. Part 2: behaviour and implications on weight reduction | 473–485 |
| Lee, Y. | Prediction of knock onset and the autoignition site in spark-ignition engines | 751–763 |
| Leung, C. W. | Multidimensional numerical simulation of heat radiation in direct injection diesel engines | 453–466 |
| Lim, W.-S. | Development of a general-purpose program based on the concept of subsystem assembly for the analysis of dynamic characteristics of a power transmission system | 545–560 |
| Liu, M. A. | Multidimensional numerical simulation of heat radiation in direct injection diesel engines | 453–466 |
| Long, T. W. | Neural network modelling of the emissions and performance of a heavy-duty diesel engine | 111–126 |
| Mahieu, V. | Idle regulation strategies using stepper motor idle valves: observation on engine simulator | 569–578 |
| Malalasekera, W. | Full-cycle firing simulation of a pent-roof spark-ignition engine with visualization of the flow structure, flame propagation and radiative heat flux | 957–971 |
| Malvicino, C. | Internal combustion engine waste heat potential for an automotive absorption system of air conditioning. Part 1: tests on the exhaust system of a spark-ignition engine | 979–982 |
| Malvicino, C. | Internal combustion engine waste heat potential for an automotive absorption system of air conditioning. Part 2: the automotive absorption system | 983–990 |
| Mansouri, S. H. | The $k$–$\varepsilon$ turbulence modelling of heat transfer and combustion processes in a Texaco controlled combustion stratified charge engine | 149–158 |
| Mao, W. | A multi-reflector headlamp that can produce a diagonal cut-off without a shield | 839–842 |
| Maskell, S. J. | Ignition source characteristics for natural-gas-burning vehicle engines | 171–180 |
| Maskell, S. J. | A comparison of the relative effects of fuel composition and ignition energy on the early stages of combustion in a natural gas spark ignition engine using simulation | 383–393 |
| Maspeyrot, P. | Comparison of the dynamic behaviour of the two misaligned crankshaft bearings | 991–997 |
| Meywerk, M. | Fluid–structure interaction in crash simulation | 669–673 |
| Miao, H. | Combustion characteristics and hydrocarbon emissions of a spark ignition engine fuelled with gasoline–oxygenate blends | 341–346 |
| Miller, J. M. | Rotational sensorless scalar control of three-phase induction motors and its application to automotive electric power assist steering | 33–44 |
| Min, K. | Prediction of the air–fuel ratio in transient conditions using a model of liquid fuel behaviour in the intake port of a spark-ignition engine | 731–740 |
| Min, K. | Prediction of knock onset and the autoignition site in spark-ignition engines | 751–763 |
| Mohan, K. R. | Performance evaluation of non-edible vegetable oils as substitute fuels in low heat rejection diesel engines | 181–187 |
| Moriyoshi, Y. | Combustion characteristics of spark-ignition and pilot flame ignition systems in a model Wankel stratified charge engine | 949–955 |



© IMechE 2000

| | | |
|---|---|---|
| Morrey, D. | Recent advances in antilock braking systems and traction control systems | 625–638 |
| Murayama, T. | Evaluating waste vegetable oils as a diesel fuel | 141–148 |
| Muroki, T. | Combustion characteristics of spark-ignition and pilot flame ignition systems in a model Wankel stratified charge engine | 949–955 |
| Naganathan, N. G. | Analysis of driveline loads in an automotive powertrain with multiple Cardan joints | 509–522 |
| Noto, T. | Evaluating waste vegetable oils as a diesel fuel | 141–148 |
| Nwagboso, C. | Fuzzy ignition timing control for a spark ignition engine | 297–306 |
| Otto, E. | Thermodynamics and charge exchange of the new BMW six-cylinder engine | 935–947 |
| Pae, S. | Prediction of knock onset and the autoignition site in spark-ignition engines | 751–763 |
| Paganelli, G. | Simulation and assessment of power control strategies for a parallel hybrid car | 705–717 |
| Pan, K. Y. | Multidimensional numerical simulation of heat radiation in direct injection diesel engines | 453–466 |
| Park, J. W. | Experimental study on the combustion characteristics of emulsified diesel in a rapid compression and expansion machine | 579–586 |
| Park, K. H. | Experimental study on the combustion characteristics of emulsified diesel in a rapid compression and expansion machine | 579–586 |
| Park, Y.-I. | Development of a general-purpose program based on the concept of subsystem assembly for the analysis of dynamic characteristics of a power transmission system | 545–560 |
| Parker, P. H. | The variable valve timing mechanism for the Rover K16 engine. Part 1: selection of the mechanism and the basis of the design | 197–205 |
| Parker, P. H. | The variable valve timing mechanism for the Rover K16 engine. Part 2: application to the engine and the performance obtained | 207–216 |
| Peyton Jones, J. C. | Stochastic prediction of cycle-by-cycle cylinder pressure fluctuations in a spark ignition engine | 435–451 |
| Phadnis, R. | Analysis of driveline loads in an automotive powertrain with multiple Cardan joints | 509–522 |
| Pilkey, W. D. | Limiting performance of seat belt systems for the prevention of thoracic injuries | 127–139 |
| Pine, T. | Automotive box section design under torsion. Part 1: finite element modelling strategy | 347–359 |
| Pine, T. | Automotive box section design under torsion. Part 2: behaviour and implications on weight reduction | 473–485 |
| Prasad, C. M. V. | Performance evaluation of non-edible vegetable oils as substitute fuels in low heat rejection diesel engines | 181–187 |
| Purdy, D. J. | Theoretical and experimental investigation into an adjustable automotive damper | 265–283 |
| Quigley, C. P. | Fuzzy modelling approach to the prediction of journey parameters for hybrid electric vehicle control | 875–885 |
| Reddy, C. P. | Performance evaluation of non-edible vegetable oils as substitute fuels in low heat rejection diesel engines | 181–187 |
| Reeves, M. | A study of brake disc modal behaviour during squeal generation using high-speed electronic speckle pattern interferometry and near-field sound pressure measurements | 285–296 |
| Ren, J. | Influence of performance characteristic of a gaseous fuel supply system on hydrocarbon emissions of a dual-fuel engine | 973–977 |
| Rhodes, C. J. | Fluctuation analysis of M25 loop data | 653–658 |
| Ro, P. I. | Reduced-order modelling and parameter estimation for a quarter-car suspension system | 851–864 |
| Roberts, J. B. | Stochastic prediction of cycle-by-cycle cylinder pressure fluctuations in a spark ignition engine | 435–451 |
| Rubbert, S. | Thermodynamics and charge exchange of the new BMW six-cylinder engine | 935–947 |
| Ryan, A. | The influence of slipstreaming on sports prototype race car performance | 887–894 |
| Santin, J.-J. | Simulation and assessment of power control strategies for a parallel hybrid car | 705–717 |
| Saran, V. H. | Rolling dynamic stiffness and damping characteristics of small-sized pneumatic tyres | 243–248 |
| Seki, K. | Comparison of the Q3 and Hybrid III 3-year-old dummy head and neck response during side air bag loading | 675–684 |
| Selim, A. M. | Performance of multicone synchronizers for manual transmissions | 55–65 |
| Sendall, P. | A study of exhaust noise in a motor vehicle using statistical energy analysis | 75–83 |
| Seneviratne, L. D. | Instantaneous friction components model for transient engine operation | 809–824 |
| Sher, E. | Vibration monitoring as a predictive maintenance tool for reciprocating engines | 895–903 |
| Shi, J. | The dimensional quality of sheet metal assembly with welding-induced internal stress | 693–704 |
| Shiu, B. W. | The dimensional quality of sheet metal assembly with welding-induced internal stress | 693–704 |
| Sims-Williams, D. B. | The influence of slipstreaming on sports prototype race car performance | 887–894 |
| Sodré, J. R. | Modelling $NO_x$ emissions from spark-ignition engines | 929–934 |
| Soliman, H. A. | Exhaust emissions from an indirect injection dual-fuel engine | 333–340 |
| Sparis, P. D. | Ambient temperature influence on catalytic outlet–inlet temperature difference | 95–110 |
| Steel, J. A. | A study of exhaust noise in a motor vehicle using statistical energy analysis | 75–83 |
| Stein, G. J. | New results on an electropneumatic active seat suspension system | 533–544 |
| Stephenson, R. | A method of measuring the dynamic loads in high-speed timing chains | 217–226 |
| Stevens, A. | Safety of driver interaction with in-vehicle information systems | 639–644 |
| Stoneman, B. | The UK road user charging technology trials: a review | 659–666 |
| Swingler, J. | The automotive connector: the influence of powering and lubricating a fretting contact interface | 615–623 |


© IMechE 2000

| | | |
|---|---|---|
| Taylor, N. | A study of brake disc modal behaviour during squeal generation using high-speed electronic speckle pattern interferometry and near-field sound pressure measurements | 285–296 |
| Thompson, G. J. | Neural network modelling of the emissions and performance of a heavy-duty diesel engine | 111–126 |
| Tse, K. H. | The dimensional quality of sheet metal assembly with welding-induced internal stress | 693–704 |
| Turner, J. D. | A review of current sensor technologies and applications within automotive and traffic control systems | 589–614 |
| Vantsevich, V. V. | Spur bevel gear differentials: designing involute tooth numbers for the pinion and side gear | 719–730 |
| Velan, T. V. T. | Fabrication and characterization of polyurethane-coated fabrics for collapsible diesel tanks | 487–491 |
| Wang, H. W. | Study on the performance and emissions of a compression ignition engine fuelled with dimethyl ether | 101–106 |
| Wang, H. W. | Investigation on emission characteristics of a compression ignition engine with oxygenated fuels and exhaust gas recirculation | 503–508 |
| Wang, W. | Fuzzy ignition control for a spark ignition engine | 297–306 |
| Wang, Z. Y. | Influence of performance characteristic of a gaseous fuel supply system on hydrocarbon emissions of a dual-fuel engine | 973–977 |
| Watts, M. J. | The development of a sub-3 litre/100 km passenger car | 827–837 |
| Whidborne, J. F. | Instantaneous friction components model for transient engine operation | 809–824 |
| Williams, D. | A study of brake disc modal behaviour during squeal generation using high-speed electronic speckle pattern interferometry and near-field sound pressure measurements | 285–296 |
| Williams, T. D. | The frontal impact response of a spaceframe chassis sportscar | 865–873 |
| Wisby, P. | Light-duty diesel exhaust after-treatment by a multicyclone particulate separator with an oxidation catalyst | 741–749 |
| Worden, K. | Differential evolution based identification of automotive hydraulic engine mount model parameters | 249–264 |
| Wyszynski, M. L. | Modelling the monolithic exhaust converter/fuel reformer reactor—a zonal approach | 905–917 |
| Xiao, Z. | The effect of aromatic hydrocarbons and oxygenates on diesel engine emissions | 307–332 |
| Xiao, Z. | Effects of fuels with a low aromatic content on diesel engine exhaust emissions | 779–794 |
| Yan, W. | A multi-reflector headlamp that can produce a diagonal cut-off without a shield | 839–842 |
| Yang, Z. L. | Investigation on emission characteristics of a compression ignition engine with oxygenated fuels and exhaust gas recirculation | 503–508 |
| Yossefi, D. | Ignition source characteristics for natural-gas-burning vehicle engines | 171–180 |
| Yossefi, D. | A comparison of the relative effects of fuel composition and ignition energy on the early stages of combustion in a natural gas spark ignition engine using simulation | 383–393 |
| Yu, F. | A study of a Kalman filter active vehicle suspension system using correlation of front and rear wheel road inputs | 493–502 |
| Zhang, J.-W. | A study of a Kalman filter active vehicle suspension system using correlation of front and rear wheel road inputs | 493–502 |
| Zhao, H. | The effect of aromatic hydrocarbons and oxygenates on diesel engine emissions | 307–332 |
| Zhao, H. | In-cylinder studies of the effects of $CO_2$ in exhaust gas recirculation on diesel combustion and emissions | 405–419 |
| Zhao, H. | Effects of fuels with a low aromatic content on diesel engine exhaust emissions | 779–794 |
| Zhong, H. | Influence of performance characteristic of a gaseous fuel supply system on hydrocarbon emissions of a dual-fuel engine | 973–977 |
| Zhou, E. | Fuzzy ignition timing control for a spark ignition engine | 297–306 |
| Zhou, L. | Combustion characteristics and hydrocarbon emissions of a spark ignition engine fuelled with gasoline–oxygenate blends | 341–346 |
| Zhou, L. B. | Study on the performance and emissions of a compression ignition engine fuelled with dimethyl ether | 101–106 |
| Zhou, L. B. | Multidimensional numerical simulation of heat radiation in direct injection diesel engines | 453–466 |
| Zhou, L. B. | Investigation on emission characteristics of a compression ignition engine with oxygenated fuels and exhaust gas recirculation | 503–508 |
| Zhou, P. L. | Heat transfer and chemical kinetics in the exhaust system of a cold-start engine fitted with a three-way catalytic converter | 765–777 |
| Zweiri, Y. H. | Instantaneous friction components model for transient engine operation | 809–824 |




© IMechE 2000